

# 3M™ Digital Projector X20/ WX20



Need the brightness and clarity of a True XGA (1024 x 768), WXGA(1280 x 800)\* LCD projector in a lightweight model that you can take on-the-go? The 3M Digital Projector X20/ WX20 may be just the right mobile solution you've been seeking. Weighing less than 4 lbs., this 2000 lumen, 4:3 aspect ratio projector delivers a crisp image from 30-300 inches - perfect for almost any office, classroom or small space screen. Easily connect your PC to one of the RGB inputs or go even lighter with a PC-less .jpg\*\* presentation using the featured USB port. You can even personalize your settings and increase your security with the many 3M X20/ WX20 features. It's lighter and brighter at it's best.



## Connections

- Computer : RGB (x2 input)
- USB : USB for remote control mouse  
USB for PC-Less presentations\*\*
- Video : S-Video  
Video Composite
- Audio : Audio In : 3.5 mini jack (x1)  
Audio Out : 3.5 mini jack (x1)

## Features

- Picture Freeze, Blank and Magnify (4x)
- Security: PIN Code Lock, My Screen Lock, Transition Detector, Kensington Lock Bar
- Adjustable Picture Mode: Normal, Cinema, Dynamic, Whiteboard, Blackboard
- Custom personalization with My Screen, My Button, My Memory features

## Basic Specs

- 2000 lumens
- XGA (1024 x 768), WX20(1280 x 800)
- 3.9 lbs / 1.784 kg
- 500 : 1 Contrast Ratio
- Digital Keystone Correction
- Aspect Ratio : 4:3 native, 16:9\*
- 3-Year Standard Warranty or 2500 hours of usage

\* for WX20 only

\*\*for X20 only

3M™ Digital Projector X20/ WX20

## Optical

Brightness	: 2000 lumens
Imager set	: 0.063", P-Si TFT Panel
Resolution (native)	: XGA (1024 x 768 pixels), WX20(1280 x 800)
Aspect ratio	: 4:3 native, 16:9*
Colors	: 16.7 million
Screen size (range)	: 30 - 300 inches
Zoom/Focus	: Manual
Zoom ratio	: 1:2:1
Projection lens : F (focal length)	: F 1.8-1.9 (f=16.4 - 19.7 mm)
Optional lenses	: No
Contrast ratio	: 500 : 1
Lamp	: 160W UHB
Lamp Life	: 2000hours(normal), up to 3000 hours (whisper)

## Electrical

Video compatibility	: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
Component signal	: 480i, 480p, 525i, 525p, 625i, 576i, 720p, 750p, 1080i, 1125i (through computer input ports)
Keystone correction	: Fixed 6:1 upward shift, auto keystone
Audio	: 1 x 1W
Noise level	: Normal 36dB, Whisper 30dB
Compatible resolution	: VGA, SVGA, XGA, SXGA, UXGA
Horizontal scan	: 31.5 - 106 kHz
Vertical scan	: 56 - 120 Hz
Power consumption	: 250W
Power supply	: Universal:100-120V/220-240V, 50/60 Hz
Regulatory approvals	: UL, cUL, FCC Part 15 Class B, CE, EN60950, WEEE
Operating temperature	: 41° - 95°F (5° - 35°C)
Storage temperature	: -4° - 140°F (-20° - 60°C)
Altitude	: Sea level to 6000 ft. (1,829 m)

## Size

Dimensions (W x H x D)	: 10.8 x 2.3 x 8.1 in (274 x 59 x 205 mm)**
Weight	: 3.9 lbs/1.784 kg

\*\*dimensions do not include elevator feet

(a) Screen size diagonal		4:3 screen							
		(b) Projection distance				(c) Screen height			
		min.		max.		down		up	
inch	m	m	inch	m	inch	cm	inch	cm	inch
30	0.8	0.8	30	0.9	36	7	3	39	15
40	1.0	1.0	40	1.2	48	9	3	52	21
50	1.3	1.3	50	1.5	61	11	4	65	26
60	1.5	1.5	61	1.9	73	13	5	78	31
70	1.8	1.8	71	2.2	85	15	6	91	36
80	2.0	2.1	81	2.5	97	17	7	105	41
90	2.3	2.3	91	2.8	110	20	8	118	46
100	2.5	2.6	102	3.1	122	22	9	131	51
120	3.0	3.1	122	3.7	147	26	10	157	62
150	3.8	3.9	153	4.7	183	33	13	196	77
200	5.1	5.2	204	6.2	245	44	17	261	103
250	6.4	6.5	255	7.8	306	54	21	327	129
300	7.6	7.8	306	9.3	368	65	26	392	154

## Warranties

Projector	: 3 Years Standard or 2500 hours of usage
Lamp	: 1 Year or 1000 hours of usage



## Accessories Included

- Power cords (x3 - US, UK, Euro)
- RGB computer cable
- RCA/Stereo mini Audio Adapter
- Remote control with 2 AA batteries
- Multi-language User's Manual
- Multi-language Operator's Guide CD
- Lens cap
- Soft Carry Case

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years from the date of purchase. **3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**

Hg-LAMP CONTAINS MERCURY. Manage in accord with disposal laws. See [www.lamprecycle.org](http://www.lamprecycle.org) or call 1-800-328-1371 (USA), 1-800-364-3577 (Canada). For product disposal see [www.eiae.org](http://www.eiae.org)

(USA) or [www.epsc.ca](http://www.epsc.ca) (Canada).

Specifications subject to change without notice.

3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

### Projection Systems Division 3M Malaysia Sdn Bhd (7251V)

Bangunan 3M  
No.6, Persiaran Tropicana  
47410 Petaling Jaya, Selangor, Malaysia.  
Tel : 03-7806 2888  
Fax : 03-7806 2895/6

[www.3m.com/meetings](http://www.3m.com/meetings)

**3M** Innovation